

Wheelock Series CVX/CSX Explosion-Proof Bells



K-75-003

Effective: April 2016

FEATURES

- **Approvals include:**
 - **UL Listed for Hazardous Atmospheres: Class I Groups B, C and D; Class II Groups F and G**
 - **California State Fire Marshal (CSFM) Listed**
- **Rugged cast mechanism enclosure with hinged cover**
- **Available in single stroke and vibrating models**
- **Models with sound output of 87 to 90 dBA**
- **Standard red enamel finish**
- **Outdoor models include protective guard**



DESCRIPTION

Kidde Fire Systems offers Eaton's Wheelock Series CVX/CSX Explosion-Proof bells for Division One applications. Bells are available for indoor or outdoor applications and in 24 VDC and 115 VAC variants.

UL LISTED FOR HAZARDOUS ATMOSPHERES

Class	Group	Contents of Hazardous Atmosphere
I	B	Hydrogen or gases and vapors of equivalent hazards, such as manufactured gas
I	C	Ethyl and ether vapors
I	D	Gasoline, petroleum, naphtha, alcohol, acetone, benzene, lacquer solvent, vapors, natural gas
II	F	Carbon black, coal, coke dust
II	G	Flour, starch, grain dusts

ORDERING INFORMATION

Part/Model Number	Where Used	Shell Size	Input Voltage	Nominal dBA at 10 Feet (Anechoic)	Current (Amps)	Mounting Options
Vibrating						
CVX10-115-R	Indoor	10 inch	115 Vac	90	.220	Note 1
CVXG10-115-R	Outdoor	10 inch	115 Vac	90	.220	Note 1
Single Stroke						
CSX10-115-R	Indoor	10 inch	115 Vac	87	.125	Note 1
CSXG10-115-R	Outdoor	10 inch	115 Vac	87	.125	Note 1
CVX10-24-R	Indoor	10 inch	24 Vdc	87	.500	Note 1
CSXG10-24-R	Outdoor	10 inch	24 Vdc	87	.500	Note 1

Note 1: All models include an integral cast backbox for surface mounting with 1/2 in. threaded conduit entrances on top and bottom of the housing.

The technical data contained herein is limited strictly for informational purposes only. Kidde-Fenwal believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever.

All trademarks are the properties of their respective owners.

EXPORT INFORMATION (USA)
Jurisdiction: EAR
US ECCN: EAR99

This literature is provided for informational purposes only. Kidde-Fenwal, Inc. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly.
If you need more information on this product, or if you have a particular question, contact Kidde-Fenwal, Inc., Ashland, MA 01721 USA.

Kidde Fire Systems
400 Main Street
Ashland, MA 01721 USA
Tel: 508.881.2000
www.kiddefiresystems.com